



## Reference Design Sheet – L502A-RBG3030 (RGBW LES18)

### Performance Specifications:

Output	Lumens [lm]	Efficacy [lm/W]	Wattage [W]
Standard	1973	83	23.7
High	2363	79	30.1

Note: All performance measurements taken @ 3000K, 100% intensity, 25°C ambient with ARK-IR-ST-LES18 and ARK-RH-LA in use

### Calibrated CCT Specs:

CCT [K]	Typical CRI
2200 (min)	80
3000	94
3500	92
4000	92
5500 (max)	85

### Diffuser Transmittance:

Diffuser	Transmittance
ARK-DF-SF2	88
ARK-DF-SF4	77
ARK-DF-SF6	70
ARK-DF-SF8	64

### Temperature Conditions:

Output	Max T [°C]
Standard Output Tc	87
High Output Tc	95
Environment Ta	40

Note: Temperature conditions applicable for 3000K, 100% intensity



Figure 1: Tc point on ORB controller, micro USB connector shield

## Recommended Thermal Management Specifications:

### Standard Output:

Thermal Interface Material: Thermal paste - PN: TC3-1G or equivalent. Alternatively, 18x18mm phase change thermal pad - PN: ARK-TM-PC1-1818  
Heat Sink: Anodized aluminum. Dissipated power(W): 48 - Thermal Resistance (°C/W): 1.1

### High Output:

Thermal Interface Material: Thermal paste - PN: TC3-1G or equivalent.  
Heat Sink: Anodized aluminum. Dissipated power(W): 57 - Thermal Resistance (°C/W): 0.9

Contact Arkalumen for validation of any other thermal interface materials. The use of gallium based paste is not recommended.

## System Inclusions:

### DMX/RDM

Order Code	LoDA	ORB	Cable	Inner Reflector	Diffuser/Holder	Firmware
<b>Z502A3030-VA1-18-X-4010</b>	L502A-RBG3030	ORB5-VA	ARK-C1-5A-30	ARK-IR-ST-LES18	ARK-RH-SA*	4010
<b>Z502A3030-VA1-18-2-4010</b>	L502A-RBG3030	ORB5-VA	ARK-C1-5A-30	ARK-IR-ST-LES18	ARK-DF-SF2	4010
<b>Z502A3030-VA1-18-4-4010</b>	L502A-RBG3030	ORB5-VA	ARK-C1-5A-30	ARK-IR-ST-LES18	ARK-DF-SF4	4010
<b>Z502A3030-VA1-18-6-4010</b>	L502A-RBG3030	ORB5-VA	ARK-C1-5A-30	ARK-IR-ST-LES18	ARK-DF-SF6	4010
<b>Z502A3030-VA1-18-8-4010</b>	L502A-RBG3030	ORB5-VA	ARK-C1-5A-30	ARK-IR-ST-LES18	ARK-DF-SF8	4010

### Casambi

Order Code	LoDA	ORB	Cable	Inner Reflector	Diffuser/Holder	Firmware
<b>Z502A3030-VWC1-18-X-4010</b>	L502A-RBG3030	ORB5-VWC	ARK-C1-2A-30	ARK-IR-ST-LES18	ARK-RH-SA*	4010
<b>Z502A3030-VWC1-18-2-4010</b>	L502A-RBG3030	ORB5-VWC	ARK-C1-2A-30	ARK-IR-ST-LES18	ARK-DF-SF2	4010
<b>Z502A3030-VWC1-18-4-4010</b>	L502A-RBG3030	ORB5-VWC	ARK-C1-2A-30	ARK-IR-ST-LES18	ARK-DF-SF4	4010
<b>Z502A3030-VWC1-18-6-4010</b>	L502A-RBG3030	ORB5-VWC	ARK-C1-2A-30	ARK-IR-ST-LES18	ARK-DF-SF6	4010
<b>Z502A3030-VWC1-18-8-4010</b>	L502A-RBG3030	ORB5-VWC	ARK-C1-2A-30	ARK-IR-ST-LES18	ARK-DF-SF8	4010

\*When selecting a system without a diffuser, an inner reflector holder (RH) will be included