



## Reference Design Sheet – L501A-RGB2040 (RGBWW LES13)

### Performance Specifications:

Output	Lumens [lm]	Efficacy [lm/W]	Wattage [W]
Standard	1180	90	13.2
High	1236	87	14.3

Note: All performance measurements taken @ 4000K, 100% intensity, 25°C ambient with ARK-IR-PL-LES13 and no diffuser in use

### Calibrated CCT Specs:

CCT [K]	Typical CRI
1800 (min)	87
3000	96
3500	96
4000	94
6500 (max)	85

### Diffuser Transmittance:

Diffuser	Transmittance
ARK-DF-SF2	95
ARK-DF-SF4	86
ARK-DF-SF6	80
ARK-DF-SF8	74

### Temperature Conditions:

Output	Max T [°C]
Standard Output Tc	68
High Output Tc	65
Environment Ta	40

Note: Temperature conditions applicable for 4000K, 100% intensity



Figure 1: Tc point on ORB controller, micro USB connector shield

## Reference Design Sheet – L501A-RGB2040 (RGBWW LES13)

### Recommended Thermal Management Specifications:

#### Standard Output:

Thermal Interface Material: Thermal paste – PN: TC3-1G or equivalent. Alternatively, 18x18mm phase change thermal pad – PN: ARK-TM-PC1-1818  
Heat Sink: Anodized aluminum. Dissipated power(W): 48 – Thermal Resistance (°C/W): 1.1

#### High Output:

Thermal Interface Material: Thermal paste – PN: TC3-1G or equivalent.  
Heat Sink: Anodized aluminum. Dissipated power(W): 57 – Thermal Resistance (°C/W): 0.9

Contact Arkalumen for validation of any other thermal interface materials. The use of gallium based paste is not recommended.

### System Inclusions:

#### DMX/RDM

Order Code	LoDA	ORB	Cable	Inner Reflector	Diffuser/Holder	Firmware
<b>Z501A2040-VA1-13-X-4010</b>	L501A-RGB2040	ORB5-VA	ARK-C1-5A-30	ARK-IR-PL-LES13	ARK-RH-SA*	4010
<b>Z501A2040-VA1-13-6-4010</b>	L501A-RGB2040	ORB5-VA	ARK-C1-5A-30	ARK-IR-PL-LES13	ARK-DF-SF6	4010

#### Casambi

Order Code	LoDA	ORB	Cable	Inner Reflector	Diffuser/Holder	Firmware
<b>Z501A2040-VWC1-13-X-4010</b>	L501A-RGB2040	ORB5-VWC	ARK-C1-2A-30	ARK-IR-PL-LES13	ARK-RH-SA*	4010
<b>Z501A2040-VWC1-13-6-4010</b>	L501A-RGB2040	ORB5-VWC	ARK-C1-2A-30	ARK-IR-PL-LES13	ARK-DF-SF6	4010

\*\*When selecting a system without a diffuser, an inner reflector holder (RH) will be included  
Other system combinations available (alternative diffusers, cables). Contact Arkalumen for all options.