

## Reference Design Sheet – L513A-RGB1840 (RGBWW LES18)

### Performance Specifications:

Output	Lumens [lm]	Efficacy [lm/W]	Wattage [W]
Standard	2506	92	27.2

Note: All performance measurements taken @ 4000K, 100% intensity, 25°C ambient with ARK-IR-ST-LES18 and no diffuser in use

### Calibrated CCT Specs:

CCT [K]	Typical CRI
1800 (min)	90
2700	93
3000	95
3500	95
4000	93
6500 (max)	84

### Diffuser Transmittance:

Diffuser	Transmittance
ARK-DF-SF2	88
ARK-DF-SF4	77
ARK-DF-SF6	70
ARK-DF-SF8	64

### Temperature Conditions:

Output	Max T [°C]
Standard Output T <sub>c</sub>	75
Environment T <sub>a</sub>	40

Note: Temperature conditions applicable for 3500K, 100% intensity




Figure 1 – T<sub>c</sub> is measured on the metal sleeve of the micro-USB programming port. To measure T<sub>c</sub>, insert thermal probe between micro-USB and top encasement of the ORB controller as shown.

## Reference Design Sheet – L513A-RGB1840 (RGBWW LES18)

### Recommended Thermal Management Specifications:

#### Standard Output:

Thermal Interface Material: Thermal paste – PN: TC3-1G or equivalent. Alternatively, 18x18mm phase change thermal pad – PN: ARK-TM-PC1-1818  
Heat Sink: Anodized aluminum. Dissipated power(W): 48 – Thermal Resistance (°C/W): 1.1

Contact Arkalumen for validation of any other thermal interface materials. The use of gallium based paste is not recommended.

### System Inclusions:

#### DMX/RDM

Order Code	LoDA	ORB	Cable	Inner Reflector	Diffuser/Holder	Firmware
<b>Z513A1840-VA1-18-X-4010</b>	L513A-RGB1840	ORB5-VA	ARK-C1-5A-30	ARK-IR-ST-LES18	ARK-RH-SA*	4010
<b>Z513A1840-VA1-18-4-4010</b>	L513A-RGB1840	ORB5-VA	ARK-C1-5A-30	ARK-IR-ST-LES18	ARK-DF-SF4	4010

#### Casambi

Order Code	LoDA	ORB	Cable	Inner Reflector	Diffuser/Holder	Firmware
<b>Z513A1840-VWC1-18-X-4010</b>	L513A-RGB1840	ORB5-VWC	ARK-C1-2A-30	ARK-IR-ST-LES18	ARK-RH-SA*	4010
<b>Z513A1840-VWC1-18-4-4010</b>	L513A-RGB1840	ORB5-VWC	ARK-C1-2A-30	ARK-IR-ST-LES18	ARK-DF-SF4	4010

\*\*When selecting a system without a diffuser, an inner reflector holder (RH) will be included  
Other system combinations available (alternative diffusers, cables). Contact Arkalumen for all options.